

HYDRAULIC PULLERS

SELF-CENTERING

BETEX HP 2/3-arm

4, 6, 8, 12, 20 & 30 ton

Capacity	4 - 30 ton
Max shaft length	185 - 360 mm
Max spread	255 - 550 mm
Stroke	60 - 111 mm



BETEX HSP 2/3-arm

4, 6, 8, 12, 20 & 30 ton

Capacity	4 - 30 ton
Max shaft length	190 - 415 mm
Max spread	315 - 620 mm
Stroke	60 - 111 mm



BETEX HXP 2/3-arm

8, 12, 20, 30 & 50 ton

Capacity	8 - 50 ton
Max shaft length	280 - 455 mm
Max spread	460 - 860 mm
Stroke	80 - 139 mm



BETEX TRI-SECTION PULLER

4, 6, 8 & 12 ton

Capacity	4 - 12 ton
Max shaft length	211 - 284 mm
Max spread	30 - 340 mm



BETEX HPP 3 in 1 Push Puller

12 ton

Capacity	8/12 ton
Spread installing	44 - 280 mm
Spread outer pulling	85 - 300 mm
Spread inner pulling	110 - 210 mm
Shaft length installing	270 mm
Shaft length outer pulling	260 mm
Shaft length inner pulling	130 - 150 mm



BETEX Bearing Splitters

4, 6, 8 & 12 ton

Capacity	4 - 12 ton
Max shaft length	250 - 380 mm
Max spread	15 - 290 mm



Accessory Set

BETEX Tri-Section Plates

6, 8, 20 & 30 ton

Capacity	6 - 30 ton
Max shaft length	110 - 415 mm
Max spread	140 - 495 mm



Accessory Set

Self-contained hydraulic 2/3-arm pullers

- ✓ Included integrated pump and cylinder
- ✓ The harder the force, the tighter the grip
- ✓ Easy to convert to 2- or 3-arm puller
- ✓ Integral safety release valve prevents overloading or exceeding max power capacity

Self-centering pullers also

- ✓ Prevents damage to shafts and workpiece being pulled
- ✓ Arms slide in- or outwards simultaneously, they cannot deflect

Compact • Strong • Safe
Versatile • Practical • Economical

MOBILE HYDRAULIC PULLERS

SELF-CENTERING

BETEX MOBIPULLER

Capacity	25 - 50 ton
Max shaft length	470 - 1150 mm
Max spread	10 - 430 mm
Stroke	260 - 460 mm



BETEX HXPM 50 ton 2-arm

Capacity	50 ton
Max shaft length	780 mm
Max spread	200 - 1250 mm
Stroke	330 mm



BETEX HXPM 50 ton 3-arm

Capacity	50 ton
Max shaft length	780 mm
Max spread	200 - 1250 mm
Stroke	330 mm



BETEX HXPM 100 ton 2-arm

Capacity	100 ton
Max shaft length	1215 mm
Max spread	200 - 1500 mm
Stroke	270 mm



BETEX HXPM 100 ton 2/3-arm

Capacity	100 ton
Max shaft length	1215 mm
Max spread	200 - 1500 mm
Stroke	270 mm



BETEX HXPM 150 ton 2/3-arm

Capacity	150 ton
Max shaft length	1150 mm
Max spread	250 - 1600 mm
Stroke	325 mm



BPP BEARING PULLER PUSHER

Max pulling cap	100 ton
Max pushing cap	68 ton
Max stroke	398 mm
Shaft diameter	120 - 178 mm



BPP BEARING PULLER PUSHER
SIDE SHIFT

Max pulling cap	100 ton
Max pushing cap	68 ton
Max stroke	255 mm
Shaft diameter	90 - 178 mm

