

■ Model No. **HYBN-160**

Height : 360 mm

Weight : 18.2 kgs

■ Specifications:

Max. Pressure : 700 bar

Oil Required : 130 cc

Max. Output : 24.13 tons / 214.7 kN

Effective stroke : 160 mm

■ Bending Capacity:

- Max. Width : 160 mm
- Max. Angle : 90 degree
- Max. Thickness : 12 mm
- Bending materials : Aluminum, Copper

■ Features:

- Vertical stand ideally suited for bending solid copper and aluminum bus bars.
- 2 lateral parallel-stops for exact angular positioning of bus bars.
- Convenient scale for reading the current bending angle.
- Single action cylinder can be uncoupled from the bending unit.
- The cylinder can also be connected to our bus bar cutting model HYBC-160.
- Operated by any hydraulic pump with rated oil pressure of 700 bar (10,000 psi).



■ Model No. **HYBN-120**

Height : 360 mm

Weight : 15.2 kgs

■ Specifications:

Max. Pressure : 700 bar

Oil Required : 124 cc

Max. Output : 24.13 tons / 214.7 kN

Effective stroke : 130 mm

■ Bending Capacity:

- Max. Width : 120 mm
- Max. Angle : 90 degree
- Max. Thickness : 12 mm
- Bending materials : Aluminum, Copper

■ Features:

- Vertical stand ideally suited for bending solid copper and aluminum bus bars.
- 2 lateral parallel-stops for exact angular positioning of bus bars.
- Convenient scale for reading the current bending angle.
- Single action cylinder can be uncoupled from the bending unit.
- The cylinder can also be connected to our bus bar cutting model HYBC-120.
- Operated by any hydraulic pump with rated oil pressure of 700 bar (10,000 psi).



■ Model No. **DBBN-120**

Height : 360 mm

Weight : 15.5 kgs

■ Specifications:

Max. Pressure : 700 bar

Oil Required : 124 cc

Max. Output : 24.13 tons / 214.7 kN

Effective stroke : 130 mm

■ Bending Capacity:

- Max. Width : 120 mm
- Max. Angle : 90 degree
- Max. Thickness : 12 mm
- Suitable materials : Aluminum, Copper

■ Features:

- Vertical stand ideally suited for bending solid copper and aluminum bus bars.
- 2 lateral parallel-stops for exact angular positioning of bus bars.
- Convenient scale for reading the current bending angle.
- Single action cylinder can be uncoupled from the bending unit.
- The cylinder can also be connected to our bus bar cutting model HYBC-120.
- Operated by any hydraulic pump with rated oil pressure of 700 bar (10,000 psi).



• Side flip

