

CUTTERS

■ Model No. **YS-30A**

Length : 481 mm

Weight : 3.9 kgs

■ Specifications:

Max. Pressure : 700 bar

Oil Required : 23 cc

Max. Output : 8.78 tons / 78.1 kN

■ Cutting Capacity:

Cu strands : 28 mm

Al strands : 28 mm

Telephone cable : 30 mm

Underground cable : 30 mm

ACSR : 19 mm

CCP cable : 30 mm

Cutting of plano wire is prohibited.

■ Features:

- Light weight portable hydraulic cutter features.
- Single action cylinder with spring return.
- Scissor type cutting for less jamming than shear type cutting.
- No set-up time required.
- Blades are easily replaceable.
- 180° degree swivel and lock pin type head allows easy cutting position.

■ Accessories:

Carrying Bag



YS-30A #7	Moving Blade
YS-30A #8	Moving Blade



■ Model No. **HYCC-85YC**

Length : 694 mm

Weight : 8.7 kgs

■ Specifications:

Max. Pressure : 700 bar

Oil Required : 80 cc

Max. Output : 8.32 tons / 74.0 kN

■ Cutting Capacity:

Cu cable : 60 mm

Al cable : 60 mm

CCP cable : 85 mm

Underground cable : 85 mm (Except armoured cable)

Cutting of plano wire is prohibited.

■ Features:

- Fast cutting with remote operation.
- Two stage pumping action for rapid blade advance.
- 180° rotating head plus an extra handle for easy carry and overhead convenient operation.
- No set-up required.

■ Accessories:

Carrying Bag



HYCC-85YC #64 Moving Blade
HYCC-85YC #65 Moving Blade

